

冠状四氟油封



代号	名称	截面图	材料	压力	温度	圆周速度	特点				
RD	冠状四氟油封		橡胶+四氟+尼龙	≤30	NBR -40至100 FKM -20至200	≤15	耐高压, 耐磨				
D	d	H	D	d	H	d	D	H	d	D	H
50	34	7.5	380	354	12.5	50	60	4.5	280	300	9.5
56	40	7.5	400	374	12.5	56	66	4.5	290	310	9.5
63	47	7.5	420	394	12.5	63	73	4.5	300	324	12.5
70	54	7.5	450	424	12.5	65	75	4.5	320	344	12.5
80	64	7.5	480	454	12.5	70	80	4.5	350	374	12.5
90	74	7.5	500	474	12.5	75	85	4.5	360	384	12.5
95	79	7.5	560	534	12.5	80	93.8	7	380	404	12.5
100	84	7.5	600	574	12.5	85	98.8	7	400	424	12.5
110	94	7.5	以上规格为孔用			90	103.8	7	420	444	12.5
115	99	7.5				95	108.8	7	450	474	12.5
120	104	7.5				100	113.8	7	480	504	12.5
125	105	9.5				110	130	9.5	500	524	12.5
130	110	9.5				115	135	9.5	550	574	12.5
140	120	9.5				120	140	9.5	560	584	12.5
150	130	9.5				125	140	9.5	600	624	12.5
160	140	9.5				130	150	9.5	以上规格为轴用		
180	160	9.5				140	160	9.5			
190	170	9.5				150	170	9.5			
200	174	12.5	160	180	9.5						
220	194	12.5	170	190	9.5						
225	199	12.5	180	200	9.5						
250	224	12.5	190	210	9.5						
280	254	12.5	200	220	9.5						
290	264	12.5	220	240	9.5						
300	274	12.5	225	245	9.5						
320	294	12.5	230	250	9.5						
350	324	12.5	250	270	9.5						